

Cisco Video Surveillance 4-Port Encoder

Product Overview

Cisco® Video Surveillance Encoders are standalone devices that can be used to convert analog video sources into digital formats so they can be integrated into a networked, IP-based video surveillance system. The 4-port model (CIVS-SENC-4P) supports four analog video inputs and can be stacked, wall mounted, or rack-mounted. A power supply is included.

Figure 1. Cisco Video Surveillance 4-Port Encoder



Protocols Supported

The 4-port encoder supports two simultaneous video streams. The streams can be compressed in H.264, MPEG-4, or MJPEG formats and in various resolution, frame-rate, and bit-rate combinations.

PTZ Interface

The encoder provides an RS-485 interface to allow for connection to PTZ control units supporting the Pelco-D protocol, in order to control PTZ functions in an external camera or PTZ mount.

Digital Inputs/ Outputs

The encoder has four digital outputs and four digital inputs to connect to and from external sensors.

Web Interface

The encoders supports Internet Explorer® 8.0 for remote setup and administration.

Video Management

The encoder connects to Cisco Video Surveillance Manager Version 6.3.2 and later.

Product Specifications

Features and Benefits

Features include the following:

- Up to D1 resolution per port
- Up to 30 frames per second (FPS) at D1 resolution (180 FPS maximum across all ports/channels)
- H.264, MPEG-4, and MJPEG compression options
- Up to two simultaneous video streams per port
- Up to five privacy mask windows per port
- Up to three motion detection windows per port

Table 1 lists product specifications for the Cisco Video Surveillance 4-Port Encoder.

Table 1. Product Specifications

General	
Analog Video Input Ports	4
Digital Alarm Inputs	4
Digital Alarm Outputs	4 (maximum voltage 12V; maximum sync 100mA)
Security	Password-protected administrative interface; HTTPS access to the administrative interface
Certifications/Ratings/Patents	CE, FCC Class B, C-Tick UL/cUL listed
Electrical	
Port	RJ-45 connector for 100/1000 BASE-TX Auto MDI/MDI-X
Cable Type	Cat5 or better
Power Input	12 VDC/24 VAC (power supply included)
Power Consumption	24W (max)
Environmental	
Operational Temperature	50° to 122°F (10° to 50°C)
Operational Humidity	20% to 80%, noncondensing
Physical	
Dimensions (LxWxH)	189 x 153 x 49.3 mm
Weight	800g
Video and Audio	
Video Encoding	H.264, MPEG-4, and MJPEG (for both PAL and NTSC)
Video Streams	Up to two simultaneous streams; the second stream is variable based on the setup of the primary stream
Audio In	RCA connector G.711 audio encoding (64 Kbps) μ-Law or A-Law mode selectable Audio input (up to 1V RMS), line-in Supports two-way audio (per channel) Supports audio mute
Audio Out	Terminal block x 4 Supports two-way audio (per channel) Mono output
PTZ Serial Interface	RS-485 Half-Duplex, supporting Pelco-D protocol

Available Resolutions

The following are the definitions of resolutions used in the table.

- **D1:** 720 x 480 (NTSC), 720 x 576 (PAL)
- **4CIF:** 704 x 480 (NTSC), 704 x 576 (PAL)
- **CIF:** 352 x 240 (NTSC), 352 x 288 (PAL)

Table 2 lists the supported primary and secondary video stream combinations on the Cisco Video Surveillance 4 Port Encoder.

Table 2. Supported Primary and Secondary Video Stream Combinations

Dual streams supported on channels 1-4	Primary stream maximum resolution	Primary maximum frame rate (fps), bit rate (Kbps), or quality/intra-frame period (S)	Secondary stream maximum resolution	Secondary maximum frame rate (fps), bit rate (Kbps,) or quality/ intra-frame period (S)
H.264 + H.264	D1	30 fps 2000 Kbps 1S	D1	15 fps 2000 Kbps 1S
H.264 + MPEG 4	D1	30 fps 2000 Kbps 1S	D1	3 fps 2000 Kbps 1S
H.264 + MJPEG	D1	30 fps 2000 Kbps 1S	D1	30 fps Good –
MPEG-4 + MJPEG	D1	20 fps Good 1S	D1	30 fps – Good
MPEG-4 + MPEG-4	D1	15 fps 2000 Kbps 1S	D1	5 fps 2000Kbps 1S
MJPEG + MJPEG	D1	30 fps Good –	D1	25 fps Good –

Table 3 shows the minimum PC client requirements.

Table 3. Minimum PC Client Requirements

Processor	Intel® Core® 2 Duo microprocessor, 2.6 GHz
Operating System	Microsoft® Windows® 7
Memory	2 GB RAM
Network Interface Card	100 megabits (or greater)
Monitor	Minimum of 1024 x 768 resolution, 16- or 32-bit pixel color resolution
Browser	Internet Explorer® 8.0, QuickTime 6.5 and later

Warranty Information

Find warranty information on Cisco.com at the [Product Warranties](#) page.

Ordering Information

Availability

The Cisco Video Surveillance 4-Port Encoder is available through Cisco Advanced Technology Provider (ATP) program partners. Table 4 lists ordering information.

Table 4. Ordering Information

Product Name	Part Number
Cisco Video Surveillance 4-Port Encoder (standalone)	CIVS-SENC-4P

Cisco Services

Cisco offers a wide range of services programs to accelerate customer success. These innovative programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, see Cisco Technical Support Services or Cisco Advanced Services.

For More Information

For more information about the Cisco Video Surveillance Encoder products, visit <http://www.cisco.com> or contact your local account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)